#### ADDENDUM

The following additional information/clarifications are issued in respect of Section IV Price Schedule Form of e-tender document relating to Bid Ref. No. SAI, LNCPE, Admin(5)/OS/HK & HORT/2019 published on 26.11.2018.

1. The technical specifications of Electrically operated equipment required as per Part B of the Price Schedule Form (page 28) are available at Annexure I,II & III as indicated below:

1	Box Sweeper	One	Annexure I (Attached)
2	Vaccum Cleaner	One	Annexure II (Attached)
3	Floor Scrubber/Buffer	One	Annexure III (Attached)

2. The words appearing in column 3 under Part C- Consumables should be corrected and read as "Quantity required per annum"

Note : Quantity indicated in the tender document is the estimated annual requirement. On this basis the bidder should quote their rate per month (ie, the rate for  $1/12^{\text{th}}$  of the estimated annual requirement) for each item and quote the amount required for each item per month.

# <u>Machines & Equipments (Electrically Operated) –</u> <u>Specifications.</u>

### 1. Box Sweeper

- Voltage: 24 Volt DC (Battery Operated)
- Sweep Width: 1000 mm or above
- Walking Speed: 0 5 Km per hour Roll
- Brush Width 575 mm Side or above
- Brush Dia: 2 X 450 mm or above
- Dustbin Capacity 85 L or above
- Power Driving Motor: 900 Watt Roll
- Brush Motor: 90 Watt X 2
- Side brush motor 2 X 98 Watt
- Dust Shaking Motor: 80 Watt
- Power of Vacuum Motor: 600 Watt 3300 rpm
- Maximum working capacity: 5000 sq meter per hour or above
- Battery 4X6 Volt 250 AH Charge time 8 hours
- Working Time 3 to 4 hours or above

## 2. Vacuum Cleaner

Particulars	Details / Values	
Suction Power (W)	400	
Motor Max. Power (W)	1,400	
Dust Capacity (L)	0.4 or above	
Noise Level (dB)	60 or below	
Dust Collection Efficiency (%)	99.99	
Head	Auto Drive Head Extendable Multi Angle Wide Brush	
Body	Carbon Light	
Hose	Smart Hose	
Extension Pipe	Carbon Light	
Unique Features	Multi Angle Head, Flat Mechanism, Quick Dust Disposal, One-Touch Zoom Pipe, Quick Storage, Handy & Easy Remote Control	
Accessories	One-Touch Swivel Brush, Quick Carrying Handle, Crevice Nozzle, Maintenance Brush	
Body Weight (kg) / Product Weight (kg)	5.6 / 7.1	
Dimension: L x W x H mm	405 x 268 x 313 or equivalent	

### 3. Floor Scrubber / Buffer

Description	Units	Values
Scrubbing width	Mm	500 to 600
Effective Suction Width	Mm	850 to 900
Theoretical area coverage	m 2 /h	2000 to 2200
Working Speed, up to	km/h	4 to 4.5
Airflow rate	L/sec	28 to 30
Vacuum Pressure	mm of H2O	1087 to 1100
Power Supply	V/Hz	230/50
Total Power	W	1400
Brush Motor	W	800
Vacuum Motor power	W	400
No. of brushes	No.	1
Diameter of brush	Mm	500 to 600
Brush Speed	rpm	180 to 200
Brush load	Kg	26
Fresh water tank	L	60 to 70
Dirty water tank	L	60 to 70
Dimensions (L x W x H)	Mm	1350 x 550 x 1120 or equivalent
Total Weight Empty	kg	80 to 120
Total Weight ready to Operate	kg	160 to 200